

# Max-sum with Quadrees for Continuous DCOPs with Application to Lane-Free Autonomous Driving

Extended Abstract

Dimitrios Troullinos  
Technical University of Crete  
Chania, Greece  
dtroullinos@dssl.tuc.gr

Vasilis Samoladas  
Technical University of Crete  
Chania, Greece  
vsam@softnet.tuc.gr

Georgios Chalkiadakis  
Technical University of Crete  
Chania, Greece  
gehalk@intelligence.tuc.gr

Markos Papageorgiou  
Technical University of Crete  
Chania, Greece  
markos@dssl.tuc.gr

## ABSTRACT

In this paper we put forward a novel extension of the classic Max-Sum algorithm to the framework of Continuous Distributed Constrained Optimization Problems (Continuous DCOPs), in which we model the exchanged messages by means of a popular geometric algorithm, Quadrees. As such, the discretization process is dynamic and embedded in the internal Max-Sum operations (addition and marginal maximization). We apply our *Max-Sum with Quadrees* approach to *Lane-Free Autonomous Driving* in a highway populated with vehicles. Our experimental evaluation verifies the efficiency of our approach in this challenging dynamic coordination domain, demonstrating its superior performance with respect to the standard Max-Sum algorithm.

## KEYWORDS

Distributed Problem Solving; Max-Sum Algorithm; Quadrees; Factor Graphs; Autonomous Driving; Lane-Free Traffic

### ACM Reference Format:

Dimitrios Troullinos, Georgios Chalkiadakis, Vasilis Samoladas, and Markos Papageorgiou. 2022. Max-sum with Quadrees for Continuous DCOPs with Application to Lane-Free Autonomous Driving: Extended Abstract. In *Proc. of the 21st International Conference on Autonomous Agents and Multiagent Systems (AAMAS 2022)*, Online, May 9–13, 2022, IFAAMAS, 3 pages.

## 1 INTRODUCTION

The framework of Distributed Constraint Optimization Problems (DCOPs) [11] is associated with a broad range of methodologies for distributed problem solving and coordination, such as Factor Graphs [8] and the Max-Sum message passing algorithm [3]. Continuous DCOPs [6, 14, 15], in which the control variables’ domain is continuous, are of particular interest corresponding as they do to a multitude of real-world settings, and posing several issues and challenges originating from the continuity of the problem domains. A host of methodologies for tackling Continuous DCOPs has been proposed in the literature, such as Local Search [14], Distributed Pseudo-tree Optimization [6]; Particle Swarm Optimization algorithms [2]; Bayesian methods [5]; and also the Max-Sum algorithm.

Proc. of the 21st International Conference on Autonomous Agents and Multiagent Systems (AAMAS 2022), P. Faliszewski, V. Mascardi, C. Pelachaud, M.E. Taylor (eds.), May 9–13, 2022, Online. © 2022 International Foundation for Autonomous Agents and Multiagent Systems (www.ifaamas.org). All rights reserved.

Existing work on Max-Sum in continuous domains makes certain assumptions regarding the factors and messages. For instance, [18] assumes access to the factors’ gradients; while [15] models factors and messages as Continuous Piecewise Linear Functions (CPLFs), which are quite restrictive, both in terms of construction (with simplices) and management. By contrast, in our approach, we model the exchanged messages with Quadrees [4], which are among the simplest geometric algorithms for data representation of a given set of points, but exhibit in general high efficiency in many applications.

Specifically, we *embed* Quadrees in the Max-Sum algorithm, to effectively achieve a fine-grained discretization of the continuous domain—the degree of which is determined by the Quadtree function approximation process itself, in an “online”, dynamic fashion. The Quadrees’ embedding in Max-Sum, is achieved via properly re-defining the necessary core Max-Sum operations (*addition* and *marginal maximization*), that are applied on the messages exchanged.

Now, the need for coordination is intense in the field of autonomous driving [13], particularly when *Lane-Free vehicle movement* [12] is assumed. In Lane-Free traffic, vehicles are no longer restricted by specific lane positioning; thus they do not perform any lane-changing operation, but rather adjust their lateral placement smoothly. This inherently continuous domain enables much higher utilization of the available road capacity, and gives rise to the design of novel techniques and methodologies, as evident by the results of [7, 10, 12, 17, 19]. A Factor Graph representation with vehicles controlling variables relating to longitudinal and lateral acceleration is natural in this domain, and allows the use of DCOPs optimization algorithms.

## 2 MAX-SUM WITH QUADTREES FOR CONTINUOUS DOMAINS

Messages in Max-Sum [3], i.e., the functions  $q_{i \rightarrow j}(x_i)$ ,  $r_{j \rightarrow i}(x_i)$ , are 1-D, since they are associated with a single scalar variable  $x_i$  (which is discrete) [3]. However, in most multiagent settings of interest, agents have more than one variables under their control—and in many cases the variables are continuous. For instance, consider the application domain of interest in our work here—that is, Lane-Free autonomous driving [12]—where vehicles need to coordinate their movement. The use of Quadrees for calculating these messages adds much desired flexibility regarding the dimensionality

of variables and messages. To this end, given a Factor Graph representation, we now model each agent  $i$  controlling a set of variables  $\mathbf{x}_i \subseteq \mathbf{x}$ , and thus all functions corresponding to the messages are now sent between factors  $j$  and agents  $i$  with dimension  $X_i = |\mathbf{x}_i|$ .

Utilizing Max-Sum in continuous domains with Quadtrees means essentially that we use them to represent a continuous function of multiple variables; and then define appropriately how the addition process is carried out, along with the marginal maximization process—as was done in [15], but in our case such operations may involve messages of higher dimensionality, represented by Quadtrees. We focus on the equations of Max-Sum, now using a vector input  $\mathbf{x}_j$  for all messages. Consider a factor  $F_j(\mathbf{s}_j)$  that depends on  $|M_j|$  variables. For messages  $r_{j \rightarrow i}^{(Qt)}(\mathbf{x}_i)$ , sent from factor  $j$  to agent  $i$ :

$$r_{j \rightarrow i}^{(Qt)}(\mathbf{x}_i) = \max_{\mathbf{s}_j | \mathbf{x}_i} \left[ F_j(\mathbf{s}_j) + \sum_{k \in N_j \setminus i} q_{k \rightarrow j}^{(Qt)}(\mathbf{x}_k) \right] \quad (1)$$

where  $(Qt)$  superscript indicates that these functions now have the form of a Quadtree representation of a real multivariate function  $f: \mathbb{R}^N \rightarrow \mathbb{R}$ . Now, the process initiates from factor  $F_j(\mathbf{s}_j)$ , which is a real multivariate function  $F_j: \mathbb{R}^n \rightarrow \mathbb{R}$ , with  $n$  being the size of vector  $\mathbf{s}_j$ . The addition and marginal maximization operations, as imposed by Eq. 1, are properly designed for Quadtree messages. Likewise, for messages  $q_{i \rightarrow j}^{(Qt)}(\mathbf{x}_i)$ , sent from agent  $i$  to factor  $j$ :

$$q_{i \rightarrow j}^{(Qt)}(\mathbf{x}_i) = a_{ij} + \sum_{k \in M_i \setminus j} r_{k \rightarrow i}^{(Qt)}(\mathbf{x}_i) \quad (2)$$

Here, we perform a summation involving many Quadtree representations,  $r_{k \rightarrow i}^{(Qt)}, \forall k \in M_i \setminus j$ , but they all depend on the same variables  $\mathbf{x}_i$ . The summation here results also in a Quadtree representation, and we obtain the final message by adding the normalization constant  $a_{ij}$ , so that  $\sum_{\mathbf{x}_i} q_{i \rightarrow j}^{(Qt)}(\mathbf{x}_i) = 0$ , the calculation of which is properly embedded within the Quadtree representation of  $q_{i \rightarrow j}^{(Qt)}(\mathbf{x}_i)$  messages. Finally, by retaining the maximum point observed on the Quadtree messages, it is quite straightforward to select the maximizing variable configuration  $\mathbf{x}_i^* = \arg \max_{\mathbf{x}_i} \sum_{k \in M_i} r_{k \rightarrow i}^{(Qt)}(\mathbf{x}_i)$ .

### 3 EXPERIMENTAL EVALUATION

We consider a highway populated with many vehicles entering from an origin point, where each vehicle possesses a desired speed parameter  $v_d$ , chosen at random within a specified speed region  $[v_{d,low}, v_{d,high}]$ . The induced speed deviations among nearby vehicles, along with heavier traffic in a Lane-Free environment, constitute a complex multi-agent environment appropriate for the application of the proposed method. Experimental evaluation is conducted using the tool of [16], an extension of the SUMO platform [9].

#### 3.1 Experimental Setup and Results

While the discretization utilized in [17] is sufficient with respect to the traffic environment settings and the safety parameters utilized in that work, we wish to highlight the superior performance of the proposed approach in intensified traffic conditions. To do so, we make the traffic environment more challenging, by adjusting the safety parameters of the factors so that vehicles employ a much more aggressive driving style (i.e., the parameters now effectively induce smaller reaction time windows and smaller safety distances).

For experimental evaluation, we used four different inflow rates  $\{5400, 7200, 9000, 12000\}$  *veh/hr* at the origin point of the highway. We compare three different approaches, specifically the “discrete Max-Sum” method for Lane-Free driving proposed in [17] (which scales to up to 9000 *veh/hr*); the same “discrete Max-Sum” model, but with the adjusted “aggressive” parameterization discussed above; and the proposed Quadtrees-employing approach, again with the more aggressive safety scheme.

Our experiments demonstrate that Quadtrees allow us to strike a balance between efficiency and safety: the vehicles are typically able to reach their desired speeds, while exhibiting *no collisions*, even for the 12000 *veh/hr* inflow rate—an unrealistically high rate for *lane-based* traffic, but now easily tackled by our approach. Of course, the induced aggressive behaviour of vehicles, also substantially improves the performance of the “discrete” approach with respect to the average speed and delay times measured, compared to the more cautious choices of [17]. Specifically, for the range of desired speeds [25, 35] *m/s*, the use of such parameters results in an improvement on average speed within the range of [1.0, 1.5] *m/s* for the inflow rates examined, which is not negligible at all, considering the range of speeds among vehicles. The increased efficiency is better depicted in the measurements of *delay*.<sup>1</sup> Specifically, we observe  $\sim 2.7$  *sec* delays for the “aggressive” discrete variant across all inflow rates, and delays ranging from 3.9 to 6.5 *sec* (depending on the inflow rate examined) for the Quadtree-employing approach. This is a more than substantial improvement when compared to the 10 to 14 *sec* delays for the “safe” discrete Max-Sum version of [17].

Yet, for the “discrete Max-Sum” cases, this improvement comes at the cost of a significant increase in collisions. Specifically, collisions for “discrete Max-Sum” increase dramatically with increasing inflow rates, ranging from 56 to 3104 collisions for the inflow rates examined. By contrast, as mentioned, vehicles employing Max-Sum with Quadtrees did not exhibit *any collisions*, while exhibiting the much improved delay times, showcasing the need for a dynamic discretization in demanding traffic conditions.

## 4 CONCLUSIONS AND FUTURE WORK

In this work, we presented an extension of the well-known Max-Sum algorithm for Continuous DCOPs, with application in the novel Lane-Free autonomous driving domain. Our results confirm that embedding Quadtrees in the Max-Sum algorithm, render the latter appropriate for demanding Continuous DCOP domains.

In future work, alternative geometric algorithms could be considered for dynamic discretization—for instance, ones that share similar characteristics with Quadtrees, such as different variants of *k-d trees* [1]. Another direction is to focus more on the convergence properties of the Max-Sum with Quadtrees approach.

## ACKNOWLEDGMENTS

The research leading to these results has received funding from the European Research Council under the European Union’s Horizon 2020 Research and Innovation programme/ ERC Grant Agreement n. [833915], project TrafficFluid.

<sup>1</sup>Delay is the difference between the actual time the vehicle spent inside the motorway, and the ideal time it would have spent with a constant speed equal to its desired speed.

## REFERENCES

- [1] Jon Louis Bentley. 1975. Multidimensional Binary Search Trees Used for Associative Searching. *Commun. ACM* 18, 9 (Sept. 1975), 509–517.
- [2] Moumita Choudhury, Saaduddin Mahmud, and Md. Mosaddek Khan. 2020. A Particle Swarm Based Algorithm for Functional Distributed Constraint Optimization Problems. *Proceedings of the AAI Conference on Artificial Intelligence* 34, 05 (Apr. 2020), 7111–7118.
- [3] Alessandro Farinelli, Alex Rogers, Adrian Petcu, and N. R. Jennings. 2008. Decentralised Coordination of Low-Power Embedded Devices Using the Max-Sum Algorithm. In *Seventh International Conference on Autonomous Agents and Multi-Agent Systems (AAMAS-08) (16/05/08)*. International Foundation for Autonomous Agents and Multiagent Systems, Richland, SC, 639–646. Event Dates: 12-16 May 2008.
- [4] Raphael A Finkel and Jon Louis Bentley. 1974. Quad trees a data structure for retrieval on composite keys. *Acta informatica* 4, 1 (1974), 1–9.
- [5] Jeroen Fransman, Joris Sijs, Henry Dol, Erik Theunissen, and Bart De Schutter. 2019. Bayesian-DPOP for Continuous Distributed Constraint Optimization Problems. In *Proceedings of the 18th International Conference on Autonomous Agents and MultiAgent Systems (Montreal QC, Canada) (AAMAS '19)*. International Foundation for Autonomous Agents and Multiagent Systems, Richland, SC, 1961–1963.
- [6] Khoi D. Hoang, William Yeoh, Makoto Yokoo, and Zinovi Rabinovich. 2020. New Algorithms for Continuous Distributed Constraint Optimization Problems. In *Proceedings of the 19th International Conference on Autonomous Agents and Multi-Agent Systems (Auckland, New Zealand) (AAMAS '20)*. International Foundation for Autonomous Agents and Multiagent Systems, Richland, SC, 502–510.
- [7] Iasson Karafyllis, Dionysis Theodosis, and Markos Papageorgiou. 2020. Using Nudging for the Control of a Non-Local PDE Traffic Flow Model. In *2020 IEEE 23rd International Conference on Intelligent Transportation Systems (ITSC)*. IEEE, Rhodes, Greece, 1–6.
- [8] Frank R Kschischang, Brendan J Frey, and Hans-Andrea Loeliger. 2001. Factor graphs and the sum-product algorithm. *IEEE Transactions on information theory* 47, 2 (2001), 498–519.
- [9] Pablo Alvarez Lopez, Michael Behrisch, Laura Bieker-Walz, Jakob Erdmann, Yun-Pang Flötteröd, Robert Hilbrich, Leonhard Lücken, Johannes Rummel, Peter Wagner, and Evamarie Wießner. 2018. Microscopic traffic simulation using sumo. In *2018 21st International Conference on Intelligent Transportation Systems (ITSC)*. IEEE, IEEE, Maui, HI, USA, 2575–2582.
- [10] Milad Malekzadeh, Ioannis Papamichail, Markos Papageorgiou, and Klaus Bogenberger. 2021. Optimal internal boundary control of lane-free automated vehicle traffic. *Transportation Research Part C: Emerging Technologies* 126 (2021), 103060.
- [11] Pragnesh Jay Modi, Wei-Min Shen, Milind Tambe, and Makoto Yokoo. 2003. An Asynchronous Complete Method for Distributed Constraint Optimization. In *Proceedings of the Second International Joint Conference on Autonomous Agents and Multiagent Systems (Melbourne, Australia) (AAMAS '03)*. Association for Computing Machinery, New York, NY, USA, 161–168.
- [12] Markos Papageorgiou, Kyriakos-Simon Mountakis, Iasson Karafyllis, Ioannis Papamichail, and Yibing Wang. 2021. Lane-Free Artificial-Fluid Concept for Vehicular Traffic. *Proc. IEEE* 109, 2 (2021), 114–121.
- [13] Scott Drew Pendleton, Hans Andersen, Xinxin Du, Xiaotong Shen, Malika Meghani, You Hong Eng, Daniela Rus, and Marcelo H Ang. 2017. Perception, planning, control, and coordination for autonomous vehicles. *Machines* 5, 1 (2017), 6.
- [14] Amit Sarker, Moumita Choudhury, and Md. Mosaddek Khan. 2021. *A Local Search Based Approach to Solve Continuous DCOs*. International Foundation for Autonomous Agents and Multiagent Systems, Richland, SC, 1127–1135.
- [15] R. Stranders, A. Farinelli, A. Rogers, and N. R. Jennings. 2009. Decentralised Coordination of Continuously Valued Control Parameters Using the Max-Sum Algorithm. In *Proceedings of The 8th International Conference on Autonomous Agents and Multiagent Systems - Volume 1 (Budapest, Hungary) (AAMAS '09)*. International Foundation for Autonomous Agents and Multiagent Systems, Richland, SC, 601–608.
- [16] Dimitrios Troullinos, Georgios Chalkiadakis, Diamantis Manolis, Ioannis Papamichail, and Markos Papageorgiou. 2021. Lane-free microscopic simulation for connected and automated vehicles. In *2021 IEEE International Intelligent Transportation Systems Conference (ITSC)*. IEEE, IEEE, Indianapolis, IN, USA, 3292–3299.
- [17] Dimitrios Troullinos, Georgios Chalkiadakis, Ioannis Papamichail, and Markos Papageorgiou. 2021. Collaborative Multiagent Decision Making for Lane-Free Autonomous Driving. In *Proceedings of the 20th International Conference on Autonomous Agents and MultiAgent Systems (AAMAS) (Virtual Event, United Kingdom)*. International Foundation for Autonomous Agents and Multiagent Systems, Virtual Event, United Kingdom, 1335–1343.
- [18] Thomas Voice, Ruben Stranders, Alex Rogers, and Nicholas R. Jennings. 2010. A Hybrid Continuous Max-Sum Algorithm for Decentralised Coordination. In *Proceedings of the 2010 Conference on ECAI 2010: 19th European Conference on Artificial Intelligence*. IOS Press, NLD, 61–66.
- [19] Venkata Karteek Yanumula, Panagiotis Typaldos, Dimitrios Troullinos, Milad Malekzadeh, Ioannis Papamichail, and Markos Papageorgiou. 2021. Optimal Path Planning for Connected and Automated Vehicles in Lane-free Traffic. In *2021 IEEE International Intelligent Transportation Systems Conference (ITSC)*. IEEE, Indianapolis, IN, USA, 3545–3552.